

ASPHERIC COEFFICIENTS

	R	k	A_4	A_6	A_8	A_{10}	A_{12}	A_{14}	A_{16}
S1	PLANO	-	-	-	-	-	-	-	-
S2	-2.859452	-1.035707	-2.745915E-03	-3.916906E-05	2.023965E-08	1.867865E-07	-	-	-

ASPHERIC LENS EQUATION

$$z = \frac{Y^2}{R(1+\sqrt{1-(1+k)Y^2/R^2})} + A_4Y^4 + A_6Y^6 + A_8Y^8 + A_{10}Y^{10} + A_{12}Y^{12} + A_{14}Y^{14} + A_{16}Y^{16}$$





SECTION A-A

NOTES/SPECIFICATIONS:

1. MATERIAL: D-LAK6
2. REFRACTIVE INDEX: 1.690 @ 587.6nm
3. DESIGN WAVELENGTH: 408 nm
4. CLEAR APERTURE:
   (S1): Ø3.45 mm
   (S2): Ø4.80 mm
5. LASER WINDOW MATERIAL: N-BK7
   WINDOW THICKNESS: 0.250 mm
   REFRACTIVE INDEX: 1.516 @ 587.6 nm
6. EFFECTIVE FOCAL LENGTH: 4.0 mm ±1.0%
7. NUMERICAL APERTURE: 0.60
8. DIAMETER TOLERANCE: ±0.015 mm
9. CENTER THICKNESS TOLERANCE: ±0.020 mm
10. SURFACE QUALITY: 40-20 SCRATCH-DIG (INCLUDES ENTIRE BULK MATERIAL)
11. RMS WFE: <0.15 λ @ 632.8 nm
12. MAGNIFICATION: INFINITE

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION		
	NAME	DATE
DRAWN	JAC	09/MAY/22
APPROVAL	DD	18/DEC/23

COPYRIGHT © 2022 BY THORLABS

VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS

THORLABS
www.thorlabs.com

0.60 NA ASPHERIC LENS,
f=4.0 mm, DW=408 nm

MATERIAL	REV
SEE NOTES	C

ITEM #	APPROX WEIGHT
357775	0.22 g