

	MATERIAL
1	N-LAK22
2	N-SF6







SECTION A-A

NOTES/SPECIFICATIONS:

1. DESIGN WAVELENGTHS: 706.5 nm, 855.0 nm, AND 1015.0 nm
2. FOCAL LENGTH: 30.0 mm±1%
3. BACK FOCAL LENGTH (REF): 27.7 mm
4. CLEAR APERTURE: >∅7.2 mm
5. SURFACE QUALITY: 40-20 SCRATCH-DIG
6. CENTRATION: <3 arcmin
7. DIAMETER TOLERANCE: +0.0/-0.1 mm
8. THICKNESS TOLERANCE: ±0.20 mm
9. COATING: BBAR Ravg <0.5% FROM 650-1050 nm, 0° AOI, ON OUTER OPTICAL SURFACES

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION		
	NAME	DATE
DRAWN	CFS	31/OCT/17
APPROVAL	WD	21/NOV/17

COPYRIGHT © 2017 BY THORLABS

VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS

THORLABS

∅8.0 mm, f = 30 mm,
NEAR IR ACHROMAT, -B COAT

MATERIAL	REV
SEE TABLE	A

ITEM #	APPROX WEIGHT
AC080-030-B	0.5 g