

	R	k	A_4	A_6	A_8	A_{10}
S1	20.199	-1	5.1910079E-6	-1.0272627E-9	-3.1622293E-12	7.6437337E-17
S2	-	-	-	-	-	-




ISOMETRIC VIEW
1 : 3

$$z = \frac{Y^2}{R(1+\sqrt{1-(1+k)Y^2/R^2})} + A_4Y^4 + A_6Y^6 + A_8Y^8 + A_{10}Y^{10}$$

ASPHERIC LENS EQUATION





SECTION A-A
SCALE 2:1

NOTES/SPECIFICATIONS:

1. REFRACTIVE INDEX AT DESIGN WAVELENGTH: 1.777
2. DESIGN WAVELENGTH: 780nm
3. FOCAL LENGTH: EFL = 26.00mm ± 1%
4. NUMERICAL APERTURE: 0.47
5. WORKING DISTANCE: 21.5mm
6. MAGNIFICATION: INFINITE
7. SURFACE QUALITY: 60-40 SCRATCH-DIG
8. RMS WFE: < 0.5 μm
9. CLEAR APERTURE (COLLIMATING): 28.0 X 28.0 mm
10. CLEAR APERTURE (FOCUSING): 28.0 X 26.2 mm
11. CENTER THICKNESS: 7.5 mm
12. COATING(S1,S2): BBAR
    350-700nm; Ravg < 0.5%
    0° AOI

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION		
	NAME	DATE
DRAWN	NG	02/21/2012
APPROVAL	PM	02/26/2012

COPYRIGHT © 2012 BY THORLABS

VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS

THORLABS
www.thorlabs.com

30mm SQUARE, CYLINDRICAL ASPHERIC LENS, EFL=26.00mm, ARC 350-700nm

MATERIAL	REV
S-LAH64	A

ITEM #	APPROX WEIGHT
AYL3026-A	19.1g