




ISOMETRIC VIEW
SCALE: 2:1







NOTES/SPECIFICATIONS:

1. CLEAR APERTURE: >10.8 x 10.8 mm
2. SURFACE FLATNESS(S1): λ/10 AT 633 nm OVER CLEAR APERTURE
3. SURFACE QUALITY (S1): 10-5 SCRATCH-DIG
   (S2): FINE GRIND
4. PARALLELISM: ≤ 3 arcmin
5. THICKNESS TOLLERANCE: ±0.20 mm
6. DIMENSION TOLERANCE: +0.00/-0.10 mm
7. DESIGN WAVELENGTH RANGE: 400-750 nm
8. COATING (S1): BROADBAND HR, DIELECTRIC
   $R_{s\ avg}$: >99% FROM 400-750 nm
   $R_{p\ avg}$: >99% FROM 400-750 nm
   AOI: 0° TO 45°
9. DAMAGE THRESHOLD: 0.250 J/cm^2 10 nm PULSE, 10 Hz AT 532 nm

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION		
	NAME	DATE
DRAWN	RJ	06/DEC/10
APPROVAL	JC	20/APR/23

COPYRIGHT © 2023 BY THORLABS

VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS

THORLABS
www.thorlabs.com

12.7 mm SQAURE BROADBAND MIRROR
400-750 nm

MATERIAL	REV
FUSED SILICA	C

ITEM #	APPROX WEIGHT
BBSQ05-E02	0.002 kg