

	PART	MATERIAL
1	354330-A	D-ZK3
2	LENS MOUNT	303 STAINLESS STEEL







SECTION A-A

NOTES/SPECIFICATIONS:
1. MATERIAL: D-ZK3
2. REFRACTIVE INDEX: 1.586 @ 587.6nm
3. DESIGN WAVELENGTH: 830 nm
4. CLEAR APERTURE (S1): ∅3.84 mm
   (S2): ∅5.00 mm
5. EFFECTIVE FOCAL LENGTH: 3.1 mm ± 1.0%
6. NUMERICAL APERTURE: 0.70
7. CENTER THICKNESS TOLERANCE: ±0.030 mm (LENS)
8. SURFACE QUALITY: 40-20 SCRATCH-DIG (INCLUDES ENTIRE BULK MATERIAL)
9. RMS WFE: ≤ DIFFRACTION LIMITED
10. COATING(S1&S2): BBAR Ravg<0.5% FROM 350-700 nm, AOI: 0°
11. FOR ASPHERIC COEFFICENTS SEE UNMOUNTED LENS, PART NUMBER 354330-A

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION		
	NAME	DATE
DRAWN	GG	14/MAR/18
APPROVAL	JAC	05/DEC/23

COPYRIGHT © 2018 BY THORLABS

VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS

THORLABS
www.thorlabs.com

MOUNTED 0.70 NA ASPHERIC LENS, f=3.1 mm, DW=830 nm, A COATED

MATERIAL	REV
SEE TABLE	C

ITEM #	APPROX WEIGHT
C330TMD-A	1.22 g