



	PART	MATERIAL
①	MECHANICAL HOUSING	BLACK ANODIZED ALUMINUM
②	MRA25-M01	N-BK7



ISOMETRIC VIEW
SCALE 1:1







NOTES/SPECIFICATIONS:

1. OPTIC IS ALIGNED FOR REFLECTED BEAMS TO EXIT AT 90° ± 20 arcmin

OPTICAL SPECIFICATIONS:

2. CLEAR APERTURE: > Ø17.5mm
3. SURFACE QUALITY: 40-20 SCRATCH-DIG
4. SURFACE FLATNESS: < λ/10 AT 633nm
5. COATING: PROTECTED GOLD, 800nm-20.0µm, Ravg: > 96%, 0° TO 45° AOI

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION		
	NAME	DATE
DRAWN	PK	25/JAN/21
APPROVAL	PH	27/MAR/24

COPYRIGHT © 2021 BY THORLABS

VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS

THORLABS
www.thorlabs.com

30 mm CAGE MOUNTED PROTECTED GOLD RIGHT ANGLE MIRROR, 800 nm-20.0 µm, M4 TAP

MATERIAL	REV
SEE TABLE	D

ITEM #	APPROX WEIGHT
CCM1-M01/M	0.085 kg