



	PART	MATERIAL
①	MECHANICAL HOUSING	BLACK ANODIZED ALUMINUM
②	MRA20-E02	N-BK7









NOTES/SPECIFICATIONS:

1. OPTIC IS ALIGNED FOR REFLECTED BEAMS TO EXIT AT 90°±20 arcmin
2. CLEAR APERTURE: ∅12.5mm

OPTICAL SPECIFICATIONS:

3. SURFACE QUALITY: 10-5 SCRATCH-DIG
4. SURFACE FLATNESS: <λ/10 AT 633nm
5. COATING: DIELECTRIC BROADBAND HR, 400-750nm, Ravg: >99%, 0° TO 45° AOI

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION		
	NAME	DATE
DRAWN	CFS	05/NOV/15
APPROVAL	DD	12/JAN/16

COPYRIGHT © 2016 BY THORLABS

VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS

THORLABS
www.thorlabs.com

16mm CAGE MOUNTED BROADBAND DIELECTRIC RIGHT ANGLE MIRROR, 400-750nm, #8-32 TAP

MATERIAL	REV
SEE TABLE	A

ITEM #	APPROX WEIGHT
CCM5-E02	0.045 kg