








SECTION A-A



NOTES/SPECIFICATIONS:

1. CLEAR APERTURE: >90% DIAMETER
2. SURFACE ACCURACY: λ/4 AT 632.8nm OVER CLEAR APERTURE
3. SURFACE QUALITY: 20-10 SCRATCH-DIG
4. BACK SURFACE: FINE GROUND
5. THICKNESS TOLERANCE: ±0.2 mm
6. DIAMETER TOLERANCE: + 0.0/-0.2 mm
7. COATING: BROADBAND HR, DIELECTRIC
   Rs and Rp >99% OVER WAVELENGTH RANGE
   AOI: 0° TO 45°

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION		
	NAME	DATE
DRAWN	MG	15/JUN/11
APPROVAL	PM	13/JUL/11

COPYRIGHT © 2010 BY THORLABS

VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS

THORLABS
www.thorlabs.com

∅12.7mm, f= 25.0mm BROADBAND MIRROR 400-750nm

MATERIAL	REV
N-BK7	A

ITEM #	APPROX WEIGHT
CM127-025-E02	0.002 kg