











NOTES/SPECIFICATIONS:

1. CLEAR APERTURE: >90% OF DIAMETER
2. SURFACE IRREGULARITY (S1): λ/4 AT 633nm OVER CLEAR APERTURE
3. BACK SURFACE (S2): UNIFORM FINE GRIND #12-#20 GRIT
4. SURFACE QUALITY: 40-20 SCRATCH-DIG
5. THICKNESS TOLERANCE: ±0.2 mm
6. DIAMETER TOLERANCE: +0.00/-0.2 mm
7. COATING: UV ENHANCED ALUMINUM, Ravg: >90% FROM 250-450nm
   AOI: 0° TO 45°

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION		
	NAME	DATE
DRAWN	EMT	19/JUL/12
APPROVAL	MG	24/JUL/12

COPYRIGHT © 2012 BY THORLABS

VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS

THORLABS
www.thorlabs.com

Ø75.0mm, f=56.25mm CONCAVE UV ENHANCED ALUMINUM MIRROR

MATERIAL	REV
N-BK7	A

ITEM #	APPROX WEIGHT
CM750-056-F01	0.1683 kg