








NOTES/SPECIFICATIONS:

1. CLEAR APERTURE: ≥ ∅ 45.7 mm
2. SURFACE QUALITY (S1, S2): 40-20 SCRATCH-DIG
3. TRANSMITTED WAVEFRONT ERROR: <λ/4 AT 633 nm
4. PARALLELISM: <3 arcmin
5. DIAMETER TOLERANCE: +0.0/-0.2 mm
6. THICKNESS TOLERANCE: ±0.1 mm
7. FILTER COATING (S1):
   REFLECTION BAND (R): >95% AVERAGE, >90% ABSOLUTE 1500-1750 nm
   TRANSMISSION BAND (T): >90% AVERAGE, >85% ABSOLUTE 1850-2100 nm
   AOI: 45°
8. AR COATING (S2):
   R: <2% ABSOLUTE 1800-2100 nm
   AOI: 45°

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION		
	NAME	DATE
DRAWN	CS	02/JAN/13
APPROVAL	MG	28/MAY/24

COPYRIGHT © 2013 BY THORLABS

VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS

THORLABS
www.thorlabs.com

∅ 50.8 mm DICHROIC MIRROR, LONGPASS, 1800 nm

MATERIAL	REV
UV FUSED SILICA	C

ITEM #	APPROX WEIGHT
DMLP1800L	20 g