





NOTES/SPECIFICATIONS:

1. CLEAR APERTURE: ≥22.5 x 32.4 mm
2. SURFACE QUALITY (S1, S2): 40-20 SCRATCH-DIG
3. TRANSMITTED WAVEFRONT ERROR: <λ/4 AT 633 nm
4. PARALLELISM: <3 arcmin
5. DIMENSIONAL TOLERANCE: ± 0.1 mm
6. FILTER COATING (S1):
   - REFLECTION BAND (R): >95% AVERAGE, >90% ABSOLUTE 380-547 nm
   - TRANSMISSION BAND (T): >90% AVERAGE, >85% ABSOLUTE 572-950 nm
   - 45° AOI
7. AR COATING (S2):
   - R: <2% ABSOLUTE 572-950 nm
   - 45° AOI

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION		
	NAME	DATE
DRAWN	MG	01/AUG/24
APPROVAL	NI	01/MAY/25

COPYRIGHT © 2024 BY THORLABS

VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS

THORLABS
www.thorlabs.com

25x36 mm LONGPASS DICHROIC MIRROR 560 nm

MATERIAL	REV
UV GRADE FUSED SILICA	A

ITEM #	APPROX WEIGHT
DMLP560R	2 g