



ISOMETRIC VIEW
SCALE 1:1





NOTES/SPECIFICATIONS:

1. CLEAR APERTURE: ≥Ø11.4 mm
2. SURFACE QUALITY (S1, S2): 40-20 SCRATCH-DIG
3. TRANSMITTED WAVEFRONT ERROR: <λ/4 AT 633 nm
4. PARALLELISM: <3 arcmin
5. DIAMETER TOLERANCE: +0.0/-0.2 mm
6. THICKNESS TOLERANCE: ±0.2 mm
7. FILTER COATING (S1):
   REFLECTION BAND (R): >99% AVERAGE Rs AND Rp 1250-1400 nm
   TRANSMISSION BAND (T): >93% AVERAGE Ts, 95% AVERAGE Tp 1000-1175 nm
   AOI: 45°
8. AR COATING (S2):
   R: <2% ABSOLUTE 1000-1175 nm
   AOI: 45°

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION		
	NAME	DATE
DRAWN	MG	03/APR/17
APPROVAL	ES	23/JUL/25

COPYRIGHT © 2017 BY THORLABS

VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS

THORLABS
www.thorlabs.com

Ø12.7 mm SHORTPASS DICHROIC MIRROR 1200 nm

MATERIAL	REV
UV FUSED SILICA	C

ITEM #	APPROX WEIGHT
DMSP1200T	1 g