








NOTES/SPECIFICATIONS:

1. CLEAR APERTURE: ≥Ø45.7 mm
2. SURFACE QUALITY (S1, S2): 40-20 SCRATCH-DIG
3. TRANSMITTED WAVEFRONT ERROR: <λ/4 AT 633 nm
4. PARALLELISM: <3 arcmin
5. DIAMETER TOLERANCE: +0.0/-0.2 mm
6. THICKNESS TOLERANCE: ±0.1 mm
7. FILTER COATING (S1):
   - REFLECTION BAND (R): >95% AVERAGE, >90% ABSOLUTE 1550-2000 nm
   - TRANSMISSION BAND (T): >90% AVERAGE, >85% ABSOLUTE 1000-1450 nm
   - AOI: 45°
8. AR COATING (S2):
   - R: <2% ABSOLUTE 932-1700 nm
   - AOI: 45°

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION		
	NAME	DATE
DRAWN	TW	17/OCT/11
APPROVAL	MG	28/MAY/24

COPYRIGHT © 2014 BY THORLABS

VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS

THORLABS
www.thorlabs.com

Ø50.8 mm DICHROIC MIRROR, SHORTPASS, 1500 nm

MATERIAL	REV
UV GRADE FUSED SILICA	G

ITEM #	APPROX WEIGHT
DMSP1500L	20 g