



1:1 ISOMETRIC VIEW FOR
REFERENCE ONLY




SECTION A-A

NOTES/SPECIFICATIONS:
1. DESIGN WAVELENGTH: 587.6nm
2. FOCAL LENGTH: f=10.00mm ± 1%
3. BACK FOCAL LENGTH(REF): bf=6.1mm
4. CLEAR APERTURE: >90% OF SURFACE LENGTH AND HEIGHT
5. SURFACE QUALITY: 60-40 SCRATCH-DIG
6. CENTRATION: ≤ 5arcmin
7. LENGTH AND HEIGHT TOLERANCE: +0.0/-0.1mm
8. THICKNESS TOLERANCE: ±0.1mm
9. SURFACE ACCURACY:
   POWER = 1 FRINGE (S1), 3 FRINGES (S2)
   IRREGULARITY = λ/4 (S1), λ (S2 H), λ/cm (S2 L)

ALL DIMENSIONS ARE IN THE FORM [in] mm.

| | NAME | DATE |
|---|---|---|
| DRAWN | BAG | 03/22/2010 |
| ENG APPR. | SG | 04/07/2010 |
| MFG APPR. | DD | 04/21/2010 |

**PROPRIETARY AND CONFIDENTIAL**

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF THORLABS, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF THORLABS, INC. IS PROHIBITED.

THORLABS INC. PO BOX 366 NEWTON NJ

TITLE:H=10.0 L=12.0 F=10.0 CYLINDRICAL N-BK7 PLANO CONVEX LENS

| MATERIAL: | SIZE | REV. |
|---|---|---|
| N-BK7 | A | C |

| SCALE: 5:1 | SHEET 1 OF 1 |
|---|---|

| DWG. NO. | PART NO. |
|---|---|
| 3658-E01 | LJ1878L1 |

5 4 3 2 1