







NOTES/SPECIFICATIONS:

1. DESIGN WAVELENGTH: 546nm
2. FOCAL LENGTH: f=8.0mm ±1%
3. BACK FOCAL LENGTH (REF): bf=4.6mm
4. CLEAR APERTURE (H x L): >6.48 x 9.90mm
5. SURFACE QUALITY (S1, S2): 60-40 SCRATCH-DIG
6. CENTRATION: ≤5arcmin
7. DIMENSIONAL TOLERANCE (H, L): +0.00/-0.10mm
8. CENTER THICKNESS TOLERANCE: ±0.10mm
9. SURFACE IRREGULARITY AT 633nm: λ (S1 H), λ/cm (S1 L), λ/4 (S2)
10. POWER TOLERANCE AT 633nm: <3λ/2 (S1), <λ/2 (S2)

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION		
	NAME	DATE
DRAWN	KMR	02/DEC/16
APPROVAL	DD	28/DEC/16

COPYRIGHT © 2016 BY THORLABS

VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS

THORLABS
www.thorlabs.com

H=7.2mm L=11.0mm F=8.0mm UVFS CYLINDRICAL PLANO-CONVEX LENS

MATERIAL	REV
UV GRADE FUSED SILICA	D

ITEM #	APPROX WEIGHT
LJ4359	1.0 g