







NOTES/SPECIFICATIONS:

1. DESIGN WAVELENGTH: 546nm
2. FOCAL LENGTH: f= -75.0mm ±1%
3. BACK FOCAL LENGTH (REF): bf= -76.6mm
4. CLEAR APERTURE (H x L): >18.00 x 27.00mm
5. SURFACE QUALITY (S1, S2): 60-40 SCRATCH-DIG
6. CENTRATION: ≤3arcmin
7. DIMENSIONAL TOLERANCE (H, L): +0.00/-0.10mm
8. CENTER THICKNESS TOLERANCE: ±0.10mm
9. SURFACE IRREGULARITY AT 633nm: λ (S1 H), λ/cm (S1 L), λ/4 (S2)
10. POWER TOLERANCE AT 633nm: <3λ/2 (S1), <λ/2 (S2)

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION		
	NAME	DATE
DRAWN	KMC	24/MAY/17
APPROVAL	DD	02/JUN/17

COPYRIGHT © 2017 BY THORLABS

VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS

THORLABS
www.thorlabs.com

H=20.0mm L=30.0mm f=-75.0mm UVFS CYLINDRICAL PLANO-CONCAVE LENS

MATERIAL	REV
UV GRADE FUSED SILICA	C

ITEM #	APPROX WEIGHT
LK4385	3.2 g