




NOTES/SPECIFICATIONS:

1. CLEAR APERTURE: > ∅22.86mm
2. SURFACE QUALITY: 20-10 SCRATCH-DIG
3. DIAMETER TOLERANCE: +0.00/-0.20mm
4. THICKNESS TOLERANCE: ±0.40mm
5. WEDGE TOLERANCE: ±10arcmin
6. FILTER COATING (S1):
   REFLECTION BAND (R): >97% AVERAGE, 400-690nm
   TRANSMISSION BAND (T): >92% AVERAGE, 710-1200nm
   0° AOI

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

| DRAWING PROJECTION | | |
|---|---|---|
| | NAME | DATE |
| DRAWN | KMR | 20/OCT/16 |
| APPROVAL | BAG | 11/DEC/20 |

COPYRIGHT © 2016 BY THORLABS

VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS

THORLABS

∅1in HIGH QUALITY
COLD MIRROR, AOI: 45°

| MATERIAL | REV |
|---|---|
| UV GRADE FUSED SILICA | C |

| ITEM # | APPROX WEIGHT |
|---|---|
| M254C45 | 5.5 g |