





NOTES/SPECIFICATIONS

1. CLEAR APERTURE: >11.43x11.43 mm
2. SURFACE QUALITY (S1): 60-40 SCRATCH-DIG
3. SURFACE FLATNESS(S1): 5λ AT 633 nm
4. ALL OTHER SURFACES FINE GROUND
5. THICKNESS TOLERANCE: ±0.20 mm
6. DIMENSIONAL TOLERANCE: +0.0/-0.20 mm
7. COATING (S1): PROTECTED SILVER
   Ravg > 96.5% FROM 450 nm - 2 µm
   Ravg > 96% FROM 2 - 20 µm
   0 TO 45° AOI

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION		
	NAME	DATE
DRAWN	SS	27/JUN/11
APPROVAL	ST	19/NOV/21

COPYRIGHT © 2021 BY THORLABS

VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS

THORLABS
www.thorlabs.com

12.7 mm SQUARE PROTECTED SILVER MIRROR, 3.2 mm THICK

MATERIAL	REV
FLOAT GLASS	E

ITEM #	APPROX WEIGHT
ME05S-P01	1.3 g