







NOTES/SPECIFICATIONS

1. CLEAR APERTURE: >45.72x45.72 mm
2. SURFACE QUALITY (S1): 60-40 SCRATCH-DIG
3. SURFACE FLATNESS: 5λ AT 633 nm
4. ALL OTHER SURFACES FINE GROUND
5. THICKNESS TOLERANCE: ±0.20 mm
6. DIMENSIONAL TOLERANCE: +0.0/-0.20 mm
7. COATING (S1): PROTECTED SILVER
   Ravg > 96.5% FROM 450 nm - 2 µm
   Ravg > 96% FROM 2 - 20 µm
   0 TO 45˚ AOI

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION		
	NAME	DATE
DRAWN	SS	27/JUN/11
APPROVAL	ST	19/NOV/21

COPYRIGHT © 2021 BY THORLABS

VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS

THORLABS
www.thorlabs.com

50.8 mm SQUARE PROTECTED SILVER MIRROR, 3.2 mm THICK

MATERIAL	REV
FLOAT GLASS	E

ITEM #	APPROX WEIGHT
ME2S-P01	20.3 g