


NOTES/SPECIFICATIONS:

1. PARENT FOCAL LENGTH: 50.8 mm ± 1%
2. REFLECTED FOCAL LENGTH: 101.6 mm ± 1% AT 90°
3. CLEAR APERTURE: >90% OF DIAMETER
4. REFLECTED WAVEFRONT ERROR: <λ/4 RMS AT 633 nm
5. SURFACE QUALITY: 40-20 SCRATCH-DIG
6. SURFACE ROUGHNESS: <100 Å RMS
7. OPTICAL COATING: PROTECTED SILVER
   - Ravg: >97% FROM 450 nm - 2 µm
   - Ravg: >95% FROM 2 µm - 20 µm
8. BLACK ANODIZED FINISH (NON-OPTICAL SURFACES)

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION		
	NAME	DATE
DRAWN	LM	25/NOV/14
APPROVAL	NI	16/JUN/23

COPYRIGHT © 2014 BY THORLABS

VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS

THORLABS
www.thorlabs.com

⌀25.4 mm, 90° OAP, RFL = 101.6 mm, PROTECTED SILVER COATED

MATERIAL	REV
6061-T6 ALUMINUM	D

ITEM #	APPROX WEIGHT
MPD149-P01	25 g