



ISOMETRIC VIEW
SCALE 3:2





NOTES/SPECIFICATIONS:

1. DIMENSIONAL TOLERANCES: ±0.1 mm
2. ANGULAR TOLERANCE: ±3 ARCMMIN
3. CLEAR APERTURE (S1, S2, S3): 70% OF FACE LENGTH AND WIDTH
4. SURFACE QUALITY (S1, S2, S3): 40-20 SCRATCH-DIG
5. SURFACE FLATNESS (S1, S2, S3): λ/10 AT 633nm (PEAK TO VALLEY) OVER CLEAR APERTURE
6. COATING (S3): MID-INFRARED ENHANCED GOLD
   Ravg: >98% FROM 2µm-20µm
   Rabs: >95% FROM 2µm-20µm
   AOI: 0° TO 45°

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION		
	NAME	DATE
DRAWN	NI	17/MAY/23
APPROVAL	PH	18/MAY/23

COPYRIGHT © 2023 BY THORLABS

VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS

THORLABS
www.thorlabs.com

10.0mm RIGHT ANGLE PRISM MID-INFRARED ENHANCED GOLD MIRROR

MATERIAL	REV
N-BK7	A

ITEM #	APPROX WEIGHT
MRA10-M02	0.001 kg