







NOTES/SPECIFICATIONS:

1. CLEAR APERTURE: 70% OF FACE LENGTH AND WIDTH
2. SURFACE QUALITY: 40-20 SCRATCH-DIG
3. SURFACE FLATNESS: λ/ 10 AT 633 nm
4. DIMENSIONAL TOLERANCES: ±0.1 mm
5. ANGULAR TOLERANCES: ±3 arcmin
6. COATING (S1): PROTECTED SILVER
   Ravg:>97% FROM 450 nm-2 µm
   Ravg:>95% FROM 2 µm-20 µm
   AOI: 0° TO 45° deg

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION		
	NAME	DATE
DRAWN	EMT	09/MAY/12
APPROVAL	NI	18/NOV/22

COPYRIGHT © 2022 BY THORLABS

VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS

THORLABS
www.thorlabs.com

25.0 mm SILVER COATED RIGHT ANGLE PRISM MIRROR

MATERIAL	REV
N-BK7	D

ITEM #	APPROX WEIGHT
MRA25-P01	0.019 kg