







NOTES/SPECIFICATIONS:

1. DESIGN WAVELENGTH RANGE: 532nm & 1064nm
2. CLEAR APERTURE: > ∅10.2mm
3. DIAMETER TOLERANCE: +0.0/-0.1mm
4. THICKNESS TOLERANCE: ±0.2mm
5. SURFACE QUALITY (S1): 10-5 SCRATCH-DIG
6. BACK SURFACE (S2): FINE GROUND
7. PARALLELISM: ≤3 arcmin
8. SURFACE FLATNESS (S1): λ/10 AT 633nm
9. COATING (S1): HR COATING
   Rs >98.0%, Rp >98.0%, 532nm, 0-45° AOI
   Rs >99.0%, Rp >99.0% 1064nm, 0-45° AOI

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION		
	NAME	DATE
DRAWN	MG	17/MAR/23
APPROVAL	BW	23/MAR/23

COPYRIGHT © 2023 BY THORLABS

VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS

THORLABS
www.thorlabs.com

∅12.7mm Nd:YAG MIRROR
λ = 532nm & 1064nm

MATERIAL	REV
FUSED SILICA	A

ITEM #	APPROX WEIGHT
NB05-K13	2 g