







NOTES/SPECIFICATIONS:

1. DESIGN WAVELENGTH RANGE: 300-308nm
2. CLEAR APERTURE: > ∅15.2mm
3. DIAMETER TOLERANCE: +0.0/-0.1mm
4. THICKNESS TOLERANCE: ±0.2mm
5. SURFACE QUALITY (S1): 10-5 SCRATCH-DIG
6. SURFACE (S2): FINE GROUND
7. SURFACE FLATNESS (S1): <λ/10 AT 633nm
8. PARALLELISM: <3 arcmin
9. COATING (S1): REFLECTIVE COATING
   Rs avg >99.5% FROM 300-308nm
   Rp avg >98.0% FROM 300-308nm
   AOI: 0˚ TO 45˚

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION		
	NAME	DATE
DRAWN	JDR	21/APR/16
APPROVAL	GG	23/JUNE/16

COPYRIGHT © 2016 BY THORLABS

VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS

THORLABS
www.thorlabs.com

∅19.0mm AR-ION LASER LINE MIRROR, λ = 300-308nm

MATERIAL	REV
FUSED SILICA	B

ITEM #	APPROX WEIGHT
NB07-K05	3.7 g