







NOTES/SPECIFICATIONS:

1. CLEAR APERTURE: > 80% DIAMETER
2. SURFACE FLATNESS (S1): λ/4 AT 632.8 nm OVER CLEAR APERTURE
3. SURFACE QUALITY (S1): 15-5 SCRATCH-DIG
4. SURFACE (S2): POLISHED
5. PARALLELISM: ≤ 3 arcmin
6. THICKNESS TOLERANCE: ±0.20 mm
7. DIAMETER TOLERANCE: +0.00/-0.10 mm
8. COATING (S1): LOW GDD COATING
   AOI: 45°
   S-POLARIZATION: R > 99%, |GDD| < 30 fs², 970 nm - 1150 nm
   P-POLARIZATION: R > 99%, |GDD| < 30 fs², 1020 nm - 1080 nm

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION		
	NAME	DATE
DRAWN	EH	11/FEB/19
APPROVAL	JE	29/MAY/19

COPYRIGHT © 2019 BY THORLABS

VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS

THORLABS
www.thorlabs.com

∅12.7 mm LOW GDD MIRROR
970 nm - 1150 nm, 45° AOI

MATERIAL	REV
FUSED SILICA	C

ITEM #	APPROX WEIGHT
UM05-45B	2 g